

BROADKILL WATERSHED

URBAN STORMWATER RUNOFF BMPs

DEFINITION

Introducing impervious surfaces (sidewalks, roofs, roads, driveways, etc.) to a landscape can substantially impact receiving streams and water bodies by increasing both stormwater runoff and its associated pollutants. Data indicates a direct relationship between the amount of imperviousness in a given watershed and the degree of degradation. That is, as imperviousness increases, degradation is also likely to increase. At present, the Broadkill Watershed has 6.7% impervious cover.

WATER QUALITY IMPACTS & TYPICAL LOADINGS

Nitrogen is a nutrient associated with the *soluble* component of stormwater runoff. Although necessary for plant growth, excess nitrogen in water becomes a pollutant, and stimulates growth of algae and other less-desirable plants. Major sources in an urban setting include fertilizers, septic systems, and atmospheric deposition. Typical loadings for total nitrogen from urban land use range from 10 to 15 lbs/ac/yr.

Phosphorus is a nutrient more often associated with the *particulate* component of stormwater runoff, since it readily attaches to sediment. Also necessary for plant growth, excess phosphorous becomes a pollutant. The major source of phosphorus in an urban setting is fertilizer. However, phosphorus can also be released into water during the construction phase of development. Some soluble phosphorus can be traced to septic systems; however, the use of low phosphorus detergents has significantly reduced this source. Typical loadings for total phosphorus from urban land uses range from 0.75 to 1.25 lbs/ac/yr.

MANAGEMENT TECHNIQUES & TYPICAL REDUCTIONS

A wide selection of best management practices (BMPs), including manmade ponds, filtration systems, and infiltration structures, can control pollutants associated with urban stormwater runoff. Until recently, however, such BMPs have largely sought to control the particulate pollutants found in surface runoff, such as sediment and those pollutants, like phosphorus, which tend to attach to sediment. Soluble pollutants on the other hand, like nitrogen, can be found in both surface runoff *and* subsurface flow. BMPs which have a vegetative component, designed for nutrient uptake and/or an anaerobic component to induce denitrification, such as constructed wetlands, biofiltration systems, and bioretention structures, can reduce these pollutants.

Current urban BMP designs remove 25 to 68 percent of total nitrogen, and 28 to 81 percent of total phosphorous.

BMP	Total Nitrogen (% reduction)	Total Phosphorus (% reduction)
Stormwater Wet Ponds	40	50
Sand Filter	47	41
Stormwater Dry Ponds	15	25
Stormwater Wetlands	30	49
Infiltration Practices	65	70
Water Quality Swales	25	34
Rain Garden	43	81

TYPICAL COSTS

Unique site conditions make “typical urban BMP costs” difficult to determine. Additionally, “per-acre-treated costs” are difficult to provide, mostly due to the economy-of-scale that affords large projects relatively lower costs. Pond construction costs, however, can provide a basis for comparisons:

- § **Residential** sites with a small project of 10-20 acres typically begin at \$25,000, whereas a large project of 100+ acres can exceed \$100,000. Median cost is about \$50,000.
- § **Commercial** sites vary greatly. Fast food restaurants or gas stations may be as small as 1 acre; Department or home-improvement stores may be around 50 acres; and shopping centers/malls can exceed 100 acres. Commercial sites typically cost \$50,000 to \$200,00. Median cost is about \$100,000.

More stringent nutrient reduction requirements, particularly for nitrogen, may increase traditional BMP costs 25 to 50 percent. Use of non-traditional techniques such as the Conservation Design approach, however, could check and, in some cases, actually reduce costs to below those for current traditional BMPs. (See CONSERVATION DESIGN FOR STORMWATER MANAGEMENT fact sheet).

One way to fund the implementation of stormwater management BMPs is through the formation of a Stormwater Utility. The user is typically assessed a fee based on the amount of impervious area their parcel contains. Based on information collected from various stormwater utilities in place around the country, fees for residential parcels range from approx. \$20-\$100 per year. Fees for commercial/institutional/industrial sites can reach the \$1,000+ range. The fees are used for operations and maintenance costs as well as capital improvement projects, depending on how the utility is structured. The Delaware Sediment & Stormwater Regulations already have statutory authority for allowing the formation of a utility in Delaware if a local jurisdiction is so inclined.

IMPLEMENTATION ISSUES

It should be noted the stormwater runoff *from particular industries*, and those *associated with new development* are enforced by different agencies. Particular industries are regulated through the federal National Pollutant Discharge Elimination System (NPDES) program, administered by the Surface Water Discharges Section within DNREC's Division of Water Resources.

The runoff associated with new development on the other hand, is regulated under the Delaware Sediment and Stormwater Regulations (the Regulations). Because of this, revisions to these regulations have been made as of early 2005. These revisions correct some minor inconsistencies with the Federal NPDES Program and assist with the implementation of non-structural stormwater management BMPs. Important examples of this include required reductions in nutrient loads if the watershed has been identified as having impaired

waterways. This is in addition to the 80% reduction of sediment load leaving the area. This section of the Regulations is imposed when a total maximum daily load (TMDL) has been set within a watershed for which pollution control strategies have been developed.

Authors: Randy Greer, Sediment & Stormwater Program,
Jennifer Bowman, Watershed Assessment Section.

BROADKILL WATERSHED

This fact sheet was prepared by the Delaware Department of Natural Resources and Environmental Control's Whole Basin Team, at the request of the Broadkill Tributary Action Teams, for citizens and stakeholders interested in one of Delaware's most environmentally and economically attractive areas—the Broadkill river and its surrounding lands, surface and ground waters.

For additional information, contact the:

Watershed Assessment Section
Department of Natural Resources and Environmental Control
820 Silver Lake Blvd., Suite 220
Dover, Delaware 19904-2464
(302) 739-9939



Delaware's good nature depends on you!

Stormwater BMP Performance

